




## Coil Drapery Mesh Specification

When ordering, please specify:

1. Weave Type
2. Wire Diameter
3. Hole Size (W)
4. Roll Width (RW)
5. Roll Length (RL)



Spiral Mesh Curtain

### Technical Parameter

|       | Opening Size |      |      | Wire D |       | Max. Open Area | Weight Kgs/m <sup>2</sup> |                 |        |
|-------|--------------|------|------|--------|-------|----------------|---------------------------|-----------------|--------|
|       | W mm         | A mm | B mm | mm     | inch  | %              | Aluminum                  | Stainless Steel | Copper |
| 3 mm  | 3            | 4    | 6    | 0.8    | 0.031 | -              | 1.17                      | 3.51            | 3.97   |
|       | 4            | 6    | 8    | 0.8    | 0.031 | -              | 0.88                      | 2.64            | 2.98   |
| 4 mm  | 4            | 6    | 8    | 1.0    | 0.039 | 61             | 1.37                      | 4.11            | 4.64   |
|       | -            | 7    | 7    | 0.8    | 0.031 | -              | 0.83                      | 2.50            | 2.81   |
| 5 mm  | 5            | 8    | 10   | 1.0    | 0.039 | 66             | 1.10                      | 3.30            | 3.73   |
|       | 6            | 9    | 12   | 1.0    | 0.039 | 70             | 1.32                      | 3.96            | 4.47   |
| 6 mm  | 6            | 9    | 12   | 1.2    | 0.047 | 70             | 1.90                      | 5.70            | 6.44   |
|       | 7            | -    | -    | 1.0    | 0.039 | 73             | 1.18                      | 3.54            | 4.00   |
| 7 mm  | 7            | -    | -    | 1.2    | 0.047 | 69             | 1.70                      | 5.10            | 5.76   |
|       | -            | 9    | 12   | 1.2    | 0.047 | 78             | 1.50                      | 4.50            | 5.08   |
|       | -            | 9    | 12   | 1.4    | 0.055 | 78             | 2.04                      | 6.12            | 6.92   |
|       | -            | 12   | 12   | 1.2    | 0.047 | 80             | 1.50                      | 4.50            | 5.08   |
|       | 9            | -    | -    | 1.6    | 0.063 | -              | 1.56                      | 4.68            | 5.29   |
| 9 mm  | 12           | -    | -    | 1.8    | 0.073 | -              | 1.83                      | 5.49            | 6.20   |
|       | 12           | -    | -    | 2.0    | 0.079 | -              | 2.26                      | 6.78            | 7.66   |
| 12 mm | 13           | -    | -    | 1.8    | 0.073 | 74             | 2.10                      | 6.30            | 7.12   |
|       | -            | 21   | 21   | 1.2    | 0.047 | 85             | 0.63                      | 1.90            | 2.15   |
|       | -            | 21   | 21   | 1.4    | 0.055 | 82             | 0.88                      | 2.65            | 3.00   |
|       | -            | 21   | 21   | 1.8    | 0.073 | 80             | 1.47                      | 4.42            | 5.00   |
| 16 mm | -            | 15   | 30   | 2.0    | 0.079 | 60             | 2.00                      | 6.00            | 6.78   |
|       | 16           | -    | -    | 3.0    | 0.118 | 66             | 4.90                      | 14.70           | 16.61  |
| 18 mm | 18           | -    | -    | 2.5    | 0.098 | 84             | 2.10                      | 6.30            | 7.12   |
|       | -            | 30   | 30   | 2.5    | 0.098 | -              | 1.77                      | 5.30            | 6.00   |