




Conical Strainers Specifications

When ordering, please specify:

1. Pipeline Size
2. Inside Diameter
3. Outside Diameter
4. Length
5. Flange Thickness



Temporary Cone Strainers

Technical Parameter

Pipeline Size DN (inch)	Flange Dimensions (Inch)						Length (Inch)			
	Inside Diameter	Outside Diameter (ASME Class 150 - 1500)					100%OA	150%OA	200%OA	300%OA
		150 lb.	300 lb.	600 lb.	900 lb.	1500 lb.				
3/4	5/8	2 1/8	2 1/2	2 1/2	2 5/8	2 5/8	2 1/4	2 1/4	3	5
1	3/4	2 1/2	2 3/4	2 3/4	3	3	2 5/8	2 3/4	3	6
1 1/2	1 1/4	3 1/8	3 1/2	3 1/2	3 3/4	3 3/4	3 1/8	4 1/2	6	9
2	1 3/4	3 7/8	4 1/8	4 1/8	5 1/2	5 1/2	3 1/2	5	7	10
2 1/2	2 1/4	4 5/8	4 7/8	4 7/8	6 3/8	6 3/8	4	6	8	11
3	2 3/4	5 1/8	5 5/8	5 5/8	6 1/2	6 3/4	4 1/2	7	9	13
4	3 1/2	5 5/8	6 7/8	7 3/8	8	8 1/8	6	10	12	18
5	4 5/8	7 1/2	8 1/4	9 1/4	9 5/8	9 7/8	8	11	14	22
6	5 1/2	8 1/2	9 5/8	10 1/4	11 1/4	11	9	13	18	25
8	7 1/8	10 3/4	11 7/8	12 3/4	14	13 3/4	12	17	23	33
10	9	13 1/8	14	15 1/2	17	17	14	22	28	41
12	10 7/8	15 7/8	16 3/8	17 3/4	19 1/2	20 3/8	16	26	34	49

Pipeline Size DN (inch)	Flange Dimensions (Inch)						Length (Inch)			
	Inside Diameter	Outside Diameter (ASME Class 150 - 1500)					100%OA	150%OA	200%OA	300%OA
		150 lb.	300 lb.	600 lb.	900 lb.	1500 lb.				
14	12 5/8	17 1/2	18 7/8	19 1/8	20 3/4	22 5/8	18	27	36	53
16	14 1/4	20	21	22	22 1/2	-	20	31	40	61
18	16 3/8	21 3/8	23 1/4	23 7/8	25	-	22	35	46	68
20	18 3/8	23 5/8	25 1/2	26 5/8	-	-	24	38	51	76
24	22 3/8	28	30 1/4	30 7/8	-	-	29	45	61	90
30	28 1/2	34 1/4	37 1/8	37 3/4	-	-	38	57	76	114
36	33	40 7/8	43 5/8	44 1/8	-	-	46	68	91	130