




Flat Wire Decorative Metal Mesh Specifications

When ordering, please specify:

1. Weave Type
2. Wire Diameter (W1 X T1, W2 x T2)
3. Hole Size (P1 x P2)
4. Roll Width (RW)
5. Roll Length (RL)



Flat Wire Mesh

Technical Parameter

	Warp Wire		Weft Wire		Open Area		Weight Kgs/m ²	
	W1 x T1 (mm)	P1 (mm)	W2 x T2 (mm)	P2 (mm)	mm	%	Stainless Steel	Copper
27.0	8.0 x 2.0	35.0	8.0 x 2.0	35.0	27.0 x 27.0	59	7.39	8.35
	8.0 x 2.0	24.0	8.0 x 2.0	24.0	16.0 x 16.0	44	10.78	12.18
16.0	6.4 x 1.0	13.4	6.4 x 1.0	13.4	7.0 x 7.0	32	7.92	8.95
	3.0 x 1.2	10.0	3.0 x 1.2	10.0	7.0 x 7.0	49	6.22	7.03
7.0	3.2 x 1.6	9.5	3.2 x 1.6	9.5	6.3 x 6.3	44	8.88	10.03
6.3	6.0 x 1.5	12.0	6.0 x 1.5	12.0	6.0 x 6.0	25	12.23	13.82
	3.0 x 0.8	9.0	3.0 x 0.8	9.0	6.0 x 6.0	41	5.30	5.99
6.0	2.2 x 0.8	6.7	2.2 x 0.8	6.7	4.5 x 4.5	45	5.10	5.76
	1.7 x 1.0	6.2	1.7 x 1.0	6.2	4.5 x 4.5	52	4.73	5.34
4.5	3.0 x 1.2	7.2	3.0 x 1.2	7.2	4.2 x 4.2	34	8.20	9.27
4.2	1.5 x 0.8	5.0	1.5 x 0.8	5.0	3.5 x 3.5	49	4.15	4.67
3.5	3.4 x 1.1	6.6	3.4 x 1.1	6.6	3.2 x 3.2	43	6.17	6.97
	3.2 x 1.2	6.4	3.2 x 1.2	6.4	3.2 x 3.2	25	9.89	11.18
3.2	10.0 x 1.0	13.0	10.0 x 1.0	13.0	3.0 x 3.0	5	13.28	15.00
3.0	2.4 x 0.9	5.1	2.4 x 0.9	5.1	2.7 x 2.7	28	7.35	8.31
2.7	4.0 x 1.0	6.5	4.0 x 1.0	6.5	2.5 x 2.5	15	10.63	12.01
2.5	7.0 x 1.0	9.0	7.0 x 1.0	9.0	2.0 x 2.0	5	13.43	15.18
2.0	1.0 x 0.5	2.5	1.0 x 0.5	2.5	1.5 x 1.5	36	3.45	3.90