





Knitted PP Wire Mesh Specifications

When ordering, please specify:


1. Weave Type
2. Wire Diameter (D)
3. Hole Size (W1 x W2)
4. Roll Width (RW)
5. Roll Length (RL)



Standard Type



High Efficient



High Penetrated

Technical Parameter

	Wire		Opening Size		Width	Length	Number of Wire
	mm	inch	mm	inch	mm	m	Nos.
100 - 120	0.15	0.0059	2 - 3	0.039 - 0.118	100 - 150	10 - 100	1 - 2
	0.17	0.0067	2 - 3	0.039 - 0.118	100 - 150	10 - 50	1 - 2
	0.19	0.0075	2 - 3	0.039 - 0.118	100 - 150	10 - 50	1 - 2
	0.21	0.0083	3 - 7	0.118 - 0.276	100 - 150	10 - 50	1 - 2
150 - 600	0.23	0.0091	3 - 7	0.118 - 0.276	150 - 600	10 - 50	1
	0.25	0.0098	3 - 7	0.118 - 0.276	150 - 600	10 - 50	1
	0.27	0.0106	3 - 7	0.118 - 0.276	150 - 600	10 - 50	1
	0.28	0.0110	3 - 7	0.118 - 0.276	150 - 600	10 - 50	1
	0.30	0.0118	3 - 7	0.118 - 0.276	150 - 600	10 - 50	1