




Slot Hole Pre-Crimped Wire Mesh Specifications

When Ordering, Please Specify:

1. Weave Type
2. Wire Diameter
3. Hole Size (L)
4. Roll Width (RW)
5. Roll Length (RL)
6. Material



Slot Hole Crimped Weave

Technical Parameter

	Opening L1 x L2		Wire D		Open Area %	Square Meter Weight (kgs)				
	mm	inch	mm	inch		Carbon Steel	Stainless Steel	Copper	Aluminum	Nickel
1.00	1.00 x 4.00	0.039 x 0.157	0.80	0.031	46.30	3.01	3.04	3.42	-	3.42
	1.00 x 5.00	0.039 x 0.197	1.00	0.039	41.67	4.11	4.15	4.67	1.41	4.66
1.20	1.20 x 7.00	0.047 x 0.276	1.00	0.039	47.73	3.57	3.61	4.06	1.23	4.05
1.50	1.50 x 4.50	0.059 x 0.177	1.00	0.039	49.09	3.59	3.62	4.08	1.23	4.07
2.00	2.00 x 6.00	0.079 x 0.236	1.20	0.047	52.08	4.01	4.05	4.55	1.38	4.54
	2.00 x 14.00	0.079 x 0.551	2.00	0.079	43.75	7.71	7.79	8.76	2.65	8.74
	2.00 x 20.00	0.079 x 0.787	1.50	0.059	53.16	4.61	4.66	5.24	1.59	5.23
2.50	2.50 x 7.50	0.098 x 0.295	1.20	0.047	58.25	3.42	3.45	3.89	1.18	3.88
3.00	3.00 x 12.00	0.118 x 0.472	2.00	0.079	51.43	6.69	6.76	7.61	2.30	7.59
4.00	4.00 x 10.00	0.157 x 0.394	2.00	0.079	55.56	6.17	6.23	7.01	2.12	6.99
	4.00 x 16.00	0.157 x 0.630	2.50	0.098	53.22	8.01	8.09	9.10	2.76	-
5.00	5.00 x 15.00	0.197 x 0.591	2.50	0.098	57.14	7.34	7.41	8.34	2.52	-
8.00	8.00 x 18.00	0.315 x 0.709	3.00	0.118	62.34	7.69	7.76	8.73	2.64	-
	8.00 x 18.00	0.315 x 0.709	3.50	0.138	58.24	10.08	10.18	11.45	3.47	-
10.00	10.00 x 20.00	0.394 x 0.787	4.00	0.157	59.52	11.16	11.27	12.68	3.84	-
	10.00 x 50.00	0.394 x 1.969	4.00	0.157	66.14	8.87	8.96	10.08	3.05	-
	10.00 x 50.00	0.394 x 1.969	5.00	0.197	60.61	13.08	13.21	14.86	4.50	-