





# Knitted Stainless Steel Wire Mesh Specifications

When ordering, please specify:


1. Weave Type
2. Wire Diameter (D)
3. Hole Size (W1 x W2)
4. Roll Width (RW)
5. Roll Length (RL)



Standard Type



High Efficient



High Penetrated

## Technical Parameter

	Wire		Opening Size		Width	Length	Number of Wire
	mm	inch	mm	inch	mm	m	Nos.
3 - 50	0.10	0.0039	1 - 3	0.039 - 0.118	3 - 50	10 - 200	1 - 3
	0.11	0.0043	1 - 3	0.039 - 0.118	3 - 80	10 - 200	1 - 3
3 - 80	0.12	0.0047	1 - 3	0.039 - 0.118	3 - 80	10 - 100	1 - 3
	0.15	0.0059	1 - 3	0.039 - 0.118	9 - 120	10 - 100	1 - 3
9 - 120	0.17	0.0067	1 - 3	0.039 - 0.118	9 - 120	10 - 50	1 - 2
	0.19	0.0075	1 - 3	0.039 - 0.118	15 - 120	10 - 50	1 - 2
15 - 120	0.21	0.0083	3 - 7	0.118 - 0.276	15 - 120	10 - 50	1 - 2
	0.23	0.0091	3 - 7	0.118 - 0.276	40 - 1000	10 - 50	1 - 2
40 - 1000	0.25	0.0098	3 - 7	0.118 - 0.276	40 - 1000	10 - 50	1 - 2
	0.27	0.0106	3 - 7	0.118 - 0.276	60 - 1000	10 - 50	1
60 - 1000	0.28	0.0110	3 - 7	0.118 - 0.276	60 - 1000	10 - 50	1
	0.30	0.0118	3 - 7	0.118 - 0.276	60 - 1000	10 - 50	1