




## Wedge Wire Screen Pipe Specifications

When ordering, please specify:

1. Pipe Diameter
2. Slot Size
3. Profile Wire
4. Support Wire
5. Pipe Length



External Circumferential Wire and Axial Internal Support Rods

### Technical Parameter

Pipe Diameter		Slot Size		Profile Wire	Support Wire	Max. Length	
inch	mm	inch	mm	type	type	ft.	m
2 7/8	73	0.008 - 0.059	0.2 - 1.5	10 TP	10 TP, 18 TP, 22 TP, Q25	19.68	3.00
3 1/2	89	0.008 - 0.059	0.2 - 1.5	18 TP, 22 TP	18 TP, 22 TP, 24 TP, Q25	19.68	6.00
4	101	0.008 - 0.079	0.2 - 2.0	18 TP, 22 TP	18 TP, 22 TP, 24 TP, Q25	19.68	6.00
4 1/2	114	0.008 - 0.079	0.2 - 2.0	18 TP, 22 TP	22 TP, 24 TP, Q25	19.68	6.00
5	127	0.008 - 0.098	0.2 - 2.5	18 TP, 22 TP	22 TP, 24 TP, Q25	19.68	6.00
6 5/8	168	0.008 - 0.098	0.2 - 2.5	18 TP, 22 TP	22 TP, 24 TP, 34 TP, Q25	19.68	6.00
7	178	0.008 - 0.098	0.2 - 2.5	18 TP, 22 TP	22 TP, 24 TP, 34 TP, Q25	19.68	6.00
8 5/8	219	0.008 - 0.098	0.2 - 2.5	22 TP, 28 TP	22 TP, 24 TP, 34 TP, Q35	39.37	12.00
9 5/8	244	0.008 - 0.098	0.2 - 2.5	22 TP, 28 TP	22 TP, 24 TP, 34 TP, Q35	39.37	12.00
10 3/4	273	0.008 - 0.098	0.2 - 2.5	22 TP, 28 TP	24 TP, 34 TP, Q35	39.37	12.00
12 3/4	324	0.008 - 0.098	0.2 - 2.5	28 TP, 34 TP	34 TP, FB 325, RD45	39.37	12.00
24	610	0.008 - 0.236	0.2 - 6.0	28 TP, 34 TP	34 TP, FB 325, RD45	19.68	6.00
36	914	0.008 - 0.354	0.2 - 9.0	28 TP, 34 TP	34 TP, FB 310, FB 325, RD45	19.68	6.00
60	1524	0.008 - 0.394	0.2 - 10.0	28 TP, 34 TP	34 TP, FB 310, FB 325, RD45	19.68	6.00