


When ordering, please specify:

1. Weave Type
2. Wire Diameter (D1 x D2)
3. Hole Size (P1 x P2)
4. Roll Width (RW)
5. Roll Length (RL)



Pre-crimp Wire and Rod Mesh

Technical Parameter

| | Items | Pre-crimp Wire | | Rods | | Open Area | | Weight Kgs/m ² | |
|--------|------------|----------------|---------|---------|---------|---------------|----|---------------------------|--------|
| | | Nos. x D1 (mm) | P1 (mm) | D2 (mm) | P2 (mm) | mm | % | Stainless Steel | Copper |
| 120/30 | HPR 120/10 | 3 X 2.75 | 125.0 | 4.0 | 14.5 | 116.75 x 10.5 | 64 | 8.26 | 9.33 |
| 100/10 | HPR 100/10 | 3 x 3.0 | 110.0 | 4.0 | 14.0 | 100.0 x 10.0 | 65 | 9.32 | 10.53 |
| | HPR 100/5 | 3 x 2.0 | 100.0 | 3.0 | 8.0 | 94.0 x 5.0 | 59 | 8.36 | 9.45 |
| 80/10 | HPR 80/10 | 3 x 2.0 | 86.0 | 3.0 | 12.0 | 80.0 x 9.0 | 65 | 8.61 | 9.73 |
| 80/7 | HPR 80/7 | 1 x 2.0 | 80.0 | 2.0 | 7.0 | 78.0 x 5.0 | 70 | 4.10 | 4.63 |
| | HPR 80/7 | 3 x 2.0 | 80.0 | 3.0 | 7.0 | 74.0 x 3.75 | 55 | 9.30 | 10.51 |
| 80/5 | HPR 80/5 | 3 x 2.0 | 80.0 | 2.5 | 5.25 | 74.0 x 3.75 | 55 | 8.50 | 9.61 |
| 70/8 | HPR 70/8 | 3 x 2.5 | 77.5 | 3.0 | 11.0 | 70.0 x 8.0 | 64 | 8.00 | 9.04 |
| 70/4 | HPR 70/4 | 3 x 2.0 | 76.0 | 2.0 | 5.5 | 70.0 x 3.5 | 56 | 7.50 | 8.48 |
| 67/17 | HPR 67/17 | 3 x 2.5 | 75.0 | 3.0 | 20.0 | 67.5 x 17.0 | 77 | 5.50 | 6.22 |
| 67/11 | HPR 67/11 | 3 x 2.5 | 75.0 | 3.0 | 14.0 | 67.5 x 11.0 | 71 | 6.00 | 6.78 |
| 67/7 | HPR 67/7 | 3 x 2.5 | 75.0 | 3.0 | 10.0 | 67.5 x 7.4 | 64 | 7.40 | 8.36 |
| 42/3 | HPR 42/3 | 4 x 2.0 | 50.0 | 3.0 | 6.0 | 42.0 x 3.0 | 42 | 11.97 | 13.53 |
| 35/4 | HPR 35/4 | 3 x 1.0 | 38.0 | 4.0 | 8.0 | 35.0 x 4.0 | 45 | 12.82 | 14.49 |
| 31/2 | HPR 31/2 | 3 x 1.25 | 35.0 | 2.0 | 4.0 | 31.0 x 2.0 | 43 | 7.38 | 8.34 |
| | HPR 31/2 | 4 x 0.75 | 34.0 | 1.5 | 3.5 | 31.0 x 2.0 | 53 | 4.30 | 4.86 |
| 23/2 | HPR 23/2 | 4X 0.75 | 26.4 | 1.5 | 3.0 | 23.4 x 1.5 | 44 | 5.20 | 5.88 |
| | HPR 23/2 | 3 x 1.0 | 26.4 | 1.6 | 3.2 | 23.4 x 1.6 | 44 | 5.80 | 6.55 |